



DSX Access Systems, Inc.

DSX-Dialup Modem SPI-1442-FI



- **RS-232 and RS-485 Outputs for Controller Communications**
- **Powered by Controllers**
- **DB9 for connections to PC**
- **Terminal Blocks for Controller Connections**
- **Over Voltage Protection**
- **Can be connected to DSX-LAN (M) for modem backup**
- **Protocol Independent**
- **Status LEDs**

DSX-Dialup Modem SPI-1442-FI

Size

SPI-1442-FI = 5.5" W x 3.5" H x 1.0" D

Weight

12.0 oz.

Temperature/Humidity

Operating 0 to 70 C

Power Requirements

DC Input Voltage 12VDC @ 300ma

Warranty

Limited 2 Years

This new DSX Modem is small and DC powered. It is easily connected to a DSX-LAN(M) module for redundancy. The unit has both an RS-232 and RS-485 communications port for connecting it to any DSX controller without the use of a MCI module or adapter. There is a DB9 connector for easy connection to a serial port. This modem comes with everything needed for any DSX dialup application.

Onboard dipswitches set PC or Controller location for modem and control speaker.

Inputs

1 – RS-232 via Terminal Block or DB25 female

Outputs

1 – RS-485 Output / 4 Wire Terminal Block